



Brands
Netatmo

Producer no.
NTH01-DE-EC

Article no.
NE1004ZZ

EAN / GTIN
3700730500258

MRP
179,99 €

- CONTROL YOUR HEATING REMOTELY from your smartphone, tablet or computer, or manually via the Thermostat. Temperature (setpoint): Range: 5 degree Celsius to 30 degree Celsius
- SMART HEATING: the Netatmo Thermostat's Auto-Adapt function optimises your comfort and consumption by switching the heating on when you need it based on your home's thermal characteristic and the outdoor temperature
- EASY TO INSTALL yourself to replace a wireless or wired thermostat. Requirements: High-speed wireless internet connection needed. App compatibility: iOS 9 minimum required, Android 4.2 minimum required, PC & Mac through the Webapp
- CONTROL YOUR HEATING ROOM BY ROOM by completing your installation with Netatmo Additional Smart Radiator Valves (sold separately)
- Compatible with HEAT PUMPS and GAS-, OIL- or WOOD-fired boilers

Designed by Philippe Starck, the Netatmo Smart Thermostat will reduce your energy consumption by 37% on average. These savings come from a heating schedule tailored to your lifestyle, coupled with easy heating controls via your smartphone and customized advice based on your Energy Savings Report.

The Smart Thermostat is also equipped with smart features to enhance the comfort of your home:

- Auto-Adapt function: anticipates when to turn the heating on based on the home's thermal characteristics and outdoor temperature;
- Return From Holiday function: effortless heating settings to have everything at the right temperature when you get home;
- Voice Control: use Siri on iPhone/iPad, Alexa on Amazon Echo or Google Assistant on Google Home to change the temperature in your home.

Complete your installation with Additional Smart Radiator Valves to save even more energy. The Netatmo Smart Thermostat can be installed in less than an hour either as a first thermostat or to replace an existing wireless or wired thermostat.

Specifications

- Programmable dry contact thermostat (ON/OFF).
- Switching current: max 4 A.
- Switching voltage: max 250 VAC.
- Switching capacity: max 120VA (4A load at 30V, 1A load at 110V/120V to 0.5A load at 220V/240V).
- Power factor: $\cos \varphi > 0.8$.
- Relay compatible with Wi-Fi 802.11 b/g/n (2.4GHz).

*Source: average reduction in energy used by Netatmo Thermostat owners in Europe from October 2015 to September 2016 when compared to installations using non-programmable thermostats. Savings by country: Belgium: 37%, France: 33%, Germany: 37%, Italy: 39%, Spain: 42%, UK: 35%

Box Contains

- 1 x Thermostat
- 1 x Mobile stand
- 1 x Relay
- 1 x Boiler adapter
- 1 x Mains adapter
- 1 x Mounting plate
- 1 x USB cable
- 4 x colour adhesives
- 3 x AAA batteries; Screws / Screws anchors